



## TECHNICAL DATA

### CABOT® WATERPROOFING CRYSTAL CLEAR #1000/ GOLDENROD #1010/SUNSET #1020/RIVER ROCK #1030 SERIES

#### DESCRIPTION

##### *Recommended Uses:*

**Cabot Waterproofing** is an advanced-technology silicone sealer that provides unsurpassed waterproofing protection to a multitude of surfaces. This convenient and simple-to-use formulation penetrates and fills the pores of the substrate with a premium-grade silicone sealer, and unlike waxes, silicone will impart a lasting repellency to any surface to which it is applied.

**Cabot Waterproofing** is for application to wood, concrete, brick, masonry and a wide-variety of porous substrates including brick, stone and unglazed tile. It is ideal for new or properly reconditioned decks, fences, siding, shingles, shakes and logs.

##### *Composition:*

Silicone Emulsion and trans-oxide colorants

##### *Finish:*

Cabot Waterproofing Crystal Clear is not toned, leaving a neutral finish – whereas Goldenrod, Sunset and River Rock have a lightly-toned appearance.

##### *Colors:*

Crystal Clear (#1000), Goldenrod (#1010), Sunset (#1020), River Rock (#1030).

##### *Tinting/Intermixing:*

Cabot Waterproofing should never be tinted. Intermixing with any of the other Cabot Waterproofing colors will achieve additional tones.

##### *Coverage:*

100-250 square feet per gallon (2.5-6.2 m<sup>2</sup>/L). Rates will vary depending on porosity of the surface.

##### *Packaging/Containers:*

Available in one-gallon containers. Crystal Clear also available in five-gallon containers.

##### *Restrictions:*

Do not apply when air or surface temperature is below 40°F or may fall below 40°F for 24 hours after application. To stain or paint over surfaces treated with Cabot Waterproofing, allow a period of up to 12 months for the surface to sufficiently weather, and always test several areas to ensure penetration and adhesion of stain or paint. Allow the surface to dry for 6 hours before contact with water. **Do not thin or combine with any other products. Do not use steel wool on surfaces that are to be coated with this product. Do not apply over painted or sealed surfaces.**

#### TECHNICAL DATA

**For Emergency Medical Information  
Contact Chem-Tel at: 1-800-255-3924**

##### *Environmental Impact:*

These products are in compliance with V.O.C. (Volatile Organic Compound) requirements under Consumer Products regulations. Call Cabot's Technical Services & Support for additional information pertaining to current V.O.C. rulings.

*Cleanup and Disposal:* Clean brushes and equipment with warm water and soap or detergent. Dispose of empty cans or unused portion in accordance with local, state, and federal regulations. Close container when not in use. Material Safety Data Sheets (MSDS) are available upon request.

##### *Physical and Chemical Data:*

*Weight:* 8.33 - 8.39 pounds per gallon

*Flash Point:* NA

*Film Thickness:* NA

*Shelf Life:* 5 years

*% Solids (weight):* 2.99 - 6.32

*% Solids (volume):* 2.98 - 5.58

*% Pigment (weight):* .11 - 1.00

*Viscosity:* Same as water

*Pigment Type:* Silicone Emulsion and Trans-Oxide pigments

*Vehicle Type:* Silicone Emulsion

*Solvent Type:* Water

*V.O.C. Content:* Less than 100 grams/liter (.84 lbs./gal.)

# CABOT® WATERPROOFING CRYSTAL CLEAR #1000/ GOLDENROD #1010/SUNSET #1020/RIVER ROCK #1030 SERIES

## APPLICATION

### *Surface Preparation:*

All surfaces should be clean, porous and free of any previous finishes. To test for porosity, apply a few drops of water to the substrate. The surface is ideal for application if water can be quickly absorbed into the substrate. Use Cabot Problem-Solver® Wood Cleaner in order to remove dirt, mildew stains, algae and other foreign matter. Use Cabot Problem-Solver Wood Brightener to easily remove extractive bleeding as well as nail and metal rust stains. Cabot Problem-Solver Wood Strippers can be used to remove coatings from surfaces to be treated. Masonry, brick, stone, clay tile and concrete patio surfaces must be clean and free of surface contaminants. New masonry, stucco and concrete must be cured for a minimum of 30 days.

**To ensure desired appearance, always apply to a small test area and allow to dry before continuing with entire project.**

### *Finishing:*

Shake container thoroughly before using. Apply liberally and evenly using a low-pressure sprayer, nylon or synthetic brush, roller, or by dipping. A low-pressure sprayer is a simple and easy method to apply this product. When using a sprayer, be sure to backbrush or roll immediately after spraying to ensure a uniform application and color distribution.

To avoid streaking when spraying vertical surfaces, start at the bottom and spray toward the top. **Apply only as much Cabot Waterproofing as the surface will absorb.** Redistribute any excess sealer that has dripped or does not penetrate into the surface after 10 minutes. Only one coat is recommended. Reapply seasonally or every 1-2 years depending on exposure. Use caution when standing or walking on surfaces still wet after the application of Cabot Waterproofing as the surface may be very slippery.

## AVAILABILITY

Cabot Wood Care Products are sold throughout the United States and Canada. For a list of Cabot dealer locations, please contact Cabot's Technical Services & Support at 1-800-US-STAIN.

## WARRANTY

If this product does not perform as stated on the label after you apply it according to label directions, Cabot will either replace this product or refund its purchase price, at its option. Cabot disclaims all other implied or expressed warranties. Cabot will not provide or pay for labor for removal or application of the product. This warranty excludes all incidental or consequential damages. This warranty gives you specific legal rights, and you may have other rights which vary from state to state.

## MAINTENANCE

Re-apply depending on exposure or wear every 1-2 years.

## TECHNICAL SERVICES

For additional technical information, product line color cards, fan decks and liquid samples, see your specialized Cabot dealer or call the Cabot Wood Care Specialists in Technical Services & Support toll-free at 1-800-US-STAIN (877-8246).

## FILING SYSTEMS

For complete model specifications and technical data on all Cabot products, visit the Cabot Home Page at: [cabotstain.com](http://cabotstain.com).



**Cabot®**  
Newburyport, MA 01950  
Tel.: 800-US-STAIN  
Fax: 1-800-998-3299  
[cabotstain.com](http://cabotstain.com)