

Material Safety Data Sheet

DATE OF PRINTING: 01/01/2010

HMIS: H2F2R1

Section 1

MANUFACTURER: PERFORMANCE COATINGS INC.
360 Lake Mendocino Drive
Ukiah, California 95482

TELEPHONE: (707) 462-3023

PRODUCT CLASS: Semitransparent Stain

CODE IDENTIFICATION: Penofin®

TRADE NAME: Penofin Ultra Premium oil – (various colors) 100 V.O.C. formula

EMERGENCY TELEPHONE NUMBERS: FOR CHEMICAL EMERGENCY. Spill, leak, fire, exposure or accident. Call CHEMTREC - Day or Night - 1-800-424-9300. Outside the United States call 202-483-7616.

EMERGENCY POISONING TREATMENT INFORMATION: Call collect 24 hours a day – 1-800-222-1222

DOT SHIPPING NAME: Non DOT regulated stain
IATA SHIPPING NAME: UN 1263, Paint Related Material, N.O.S., 3, III
IMDG SHIPPING NAME: UN1263, Paint Related Material, N.O.N., 3, III

Section 2 - Hazardous Ingredients

	PERCENT BY WEIGHT	ACGIH TLV* PPM mg./m3	OSHA PEL* PPM mg./m3
142 Solvent CAS Number 064742-88-7	5.09%	100 PPM	100 PPM
Xylene CAS Number 1330-20-7	1.78%	100 PPM	100 PPM
Ethyl Benzene CAS Number 100-41-4	.35%	100 PPM	100 PPM

*Threshold Limit Value *Permissible Exposure Limit

Section 3 - Physical Data

BOILING RANGE: 279 °F VAPOR DENSITY: Heavier than Air.
EVAPORATION RATE: Slower than ether. WEIGHT PER GALLON: 7.8
PERCENT VOLATILE BY VOLUME: 22.71% VAPOR PRESSURE: 5.1 MM Hg@20°
MELTING POINT: Not applicable. VOCs: <100 grams/liter
SOLUBILITY IN WATER: Insoluble
APPEARANCE AND ODOR: Colored liquid with mineral solvent odor; irritating odor at high concentrations.

Section 4 - Fire and Explosion Hazard Data

OSHA CATEGORY: Combustible Class II
FLASH POINT: 122°F Tag Closed Cup LEL%: 1.0 UEL%: 12.3

To avoid spontaneous combustion, soak oily cloths, brushes, rollers, etc. in water after use or place in a closed metal container away from building and other combustible materials. Dispose of in accordance with local regulations.

EXTINGUISHING MEDIA: Foam, CO₂, dry chemical.

UNUSUAL FIRE OR EXPLOSION HAZARDS: Keep away from heat, sparks, or open flame.

SPECIAL FIRE FIGHTING PROCEDURES: Positive pressure self-contained breathing apparatus (SCBA) should be worn to avoid inhalation of concentrated vapors. Chemical protective clothing is recommended if there may be repeated or prolonged exposure to the liquid or concentrated vapors.

Section 5 - Health Hazard Data

THRESHOLD LIMIT VALUE: See Section II

PRIMARY ROUTE(S) OF ENTRY: Dermal, ingestion, inhalation.

EFFECTS OF OVEREXPOSURE: Acute -Eye or skin contact may cause irritation. Can be irritating to the respiratory tract if inhaled as a mist or concentrated vapor. Inhalation of the vapors, or ingestion of the liquid, can cause systemic toxicity including dizziness, confusion, drowsiness, incoordination, staggering gait, nausea, headache, or even collapse and coma. Ingestion may also lead to chemical pneumonia if the material is aspirated into the lungs.

Chronic -Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain damage and nervous system damage.

Section 5 - Health Hazard Data (Cont'd)

EMERGENCY FIRST AID PROCEDURES:

INHALATION: Move to fresh air.

SKIN: Promptly remove contaminated clothing and wash with soap and water.

EYES: Irrigate immediately with water or saline for at least 10-15 minutes.

INGESTION: Do not induce vomiting. Call a physician immediately and/or transport to emergency facility immediately.

Section 6 - Reactivity Data

STABILITY: (Conditions to avoid) Avoid open flames, welding arcs or other high temperature sources which induce thermal decomposition. Avoid strong oxidants.

HAZARDOUS DECOMPOSITION PRODUCTS: May form: carbon dioxide, carbon monoxide, and various hydrocarbons.

HAZARDOUS POLYMERIZATION: Will not occur.

Section 7 - Spill or Leak Procedure

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: **SMALL LEAKS:** Mop up, wipe up, or soak up immediately remove to out-of-doors.

LARGE SPILLS: Evacuate area. Contain liquid; transfer to closed metal containers. Keep out of water supplies.

DISPOSAL METHOD: When disposing of the unused contents, the preferred options are to send to licensed reclaimer, or to permitted incinerators. Any disposal practice must be in compliance with federal, state and local regulations. Do not dump into sewers, on the ground, or into any body of water.

Section 8 - Special Protection Information

RESPIRATORY PROTECTION: Use a supplied air respirator when airborne exposure limits are exceeded.

VENTILATION: Control airborne concentrations below the exposure guideline. Use only with adequate ventilation. Local exhaust ventilation may be necessary for some operations. Lethal concentrations may exist in areas with poor ventilation.

Section 8 - Special Protection Information (cont'd)

SKIN PROTECTION: For brief contact, no precautions other than clean body-covering clothing should be needed. When prolonged or frequently repeated contact could occur, use protective clothing impervious to this material. Selection of specific items such as gloves, boots, apron, or fully body suit will depend on operation.

EYE PROTECTION: Use safety glasses. Where contact with liquid is likely, chemical goggles are recommended.

OTHER PROTECTIVE EQUIPMENT: It is suggested that a source of clean water be available in work area for flushing eyes and skin.

Section 9 - Special Precautions

PRECAUTIONS TO BE TAKEN IN HANDLING OR STORING: Do not store above 125 °F.

OTHER PRECAUTIONS: Do not take internally. Do not use in areas of inadequate ventilation.

Section 10 - Sara 313 Information

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR Part 372:

<u>CHEMICAL NAME</u>	<u>CAS NUMBER</u>	<u>% BY WEIGHT</u>
Xylene	1330-20-7	1.78%
Ethyl Benzene	100-41-4	.35%

PREPARED BY: Regulatory Director, Performance Coatings Inc., Ukiah, California 95482

REFERENCE DATE: July 2007

WARNING

Detectable amounts of some chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm may be found in various petroleum products and chemical products you purchase from Performance Coatings Inc., in their vapors, or may result from their use. Use care when handling or using all chemical and petroleum products.

THE INFORMATION AND RECOMMENDATIONS CONTAINED HEREIN ARE BASED UPON DATA BELIEVED TO BE CORRECT. HOWEVER, NO GUARANTEE OR WARRANTY OF ANY KIND EXPRESSED OR IMPLIED IS MADE WITH RESPECT TO THE INFORMATION CONTAINED HEREIN.