

SECTION 1

PRODUCT IDENTIFIER SIK56100 SIKKENS RUBBOL SIDING FINISH-100 WHITE
 DATE OF PREPARATION JANUARY 23, 2009
 PRODUCT USE PROTECTIVE COATING
 MANUFACTURED BY: AKZO NOBEL PAINTS LLC, 15885 WEST SPRAGUE ROAD,
 STRONGSVILLE, OHIO 44136, U.S.A
 ICI PAINTS (CANADA), 8200 KEELE STREET,
 CONCORD, ONTARIO L4K 2A5, CANADA.
 EMERGENCY AND MSDS TELEPHONE NUMBER:
 1-800-545-2643
 MSDS PREPARED BY: PRODUCT SAFETY AND COMPLIANCE DEPARTMENT
 AKZO NOBEL PAINTS LLC

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

	INGREDIENT	WT. %:
CHEMICAL NAME	ACRYLIC RESIN	10-20
COMMON NAME :	ACRYLIC RESIN	
CAS NUMBER:	CONFIDENTIAL	
CHEMICAL NAME	SILICA GEL, PRECIPITATED, CRYSTALLINE-FREE	1-5
COMMON NAME :	SILICA, GEL, AMORPHOUS	
CAS NUMBER:	112926-00-8	
CHEMICAL NAME	TITANIUM OXIDE	10-20
COMMON NAME :	TITANIUM DIOXIDE	
CAS NUMBER:	13463-67-7	
CHEMICAL NAME	PROPANOIC ACID, 2-METHYL-, MONOESTER WITH 2,2,4-TRIMETHYL-1,3-PENTANEDIOL	1-5
COMMON NAME :	TEXANOL	
CAS NUMBER:	25265-77-4	
CHEMICAL NAME	1,2-PROPANEDIOL	1-5
COMMON NAME :	PROPYLENE GLYCOL	
CAS NUMBER:	57-55-6	
CHEMICAL NAME	SOYBEAN OIL, POLYMER WITH PENTAERYTHRITOL AND PHTHALIC ANHYDRIDE	1-5
COMMON NAME :	ALKYD RESIN	
CAS NUMBER:	66070-60-8	
CHEMICAL NAME	WATER	50-60
COMMON NAME :	WATER	
CAS NUMBER:	7732-18-5	

SECTION 3: HAZARDS IDENTIFICATION

PRIMARY ROUTE(S) OF EXPOSURE
 INHALATION, SKIN CONTACT, EYE CONTACT, INGESTION.

EFFECTS OF OVEREXPOSURE

INHALATION IRRITATION OF LUNGS. PROLONGED INHALATION MAY LEAD TO
 DIZZINESS AND/OR LIGHTHEADEDNESS, HEADACHE, UNCOORDINATION,
 NAUSEA, COUGHING, LOSS OF CONSCIOUSNESS.

SKIN CONTACT IRRITATION OF SKIN. PROLONGED OR REPEATED CONTACT CAN CAUSE
 DERMATITIS. POSSIBLE SENSITIZATION TO SKIN. SKIN CONTACT
 MAY RESULT IN DERMAL ABSORPTION OF COMPONENT(S) OF THIS
 PRODUCT WHICH MAY CAUSE HEADACHE, NAUSEA, CENTRAL NERVOUS
 SYSTEM DEPRESSION.

EYE CONTACT IRRITATION OF EYES. PROLONGED OR REPEATED CONTACT CAN CAUSE
 TEARING OF EYES.

INGESTION INGESTION MAY CAUSE MOUTH AND THROAT IRRITATION, NAUSEA,
 VOMITING, DIARRHEA, GASTRO-INTESTINAL DISTURBANCES, CENTRAL
 NERVOUS SYSTEM DEPRESSION, KIDNEY DAMAGE.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE
 EYE, SKIN, RESPIRATORY DISORDERS.

SECTION 4: FIRST-AID MEASURES

INHALATION REMOVE TO FRESH AIR. RESTORE AND SUPPORT CONTINUED
 BREATHING.

GET EMERGENCY MEDICAL ATTENTION.
 HAVE TRAINED PERSON GIVE OXYGEN IF NECESSARY. GET MEDICAL
 HELP FOR ANY BREATHING DIFFICULTY.
 REMOVE TO FRESH AIR IF INHALATION CAUSES EYE WATERING,
 HEADACHES, DIZZINESS, OR OTHER DISCOMFORT.
 SKIN CONTACT WASH THOROUGHLY WITH SOAP AND WATER. IF ANY PRODUCT REMAINS,
 GENTLY RUB PETROLEUM JELLY, VEGETABLE OR MINERAL/BABY OIL
 ONTO SKIN. REPEATED APPLICATIONS MAY BE NEEDED. REMOVE
 CONTAMINATED CLOTHING.
 WASH CONTAMINATED CLOTHING BEFORE RE-USE.
 DISPOSE OF CONTAMINATED LEATHER ITEMS, SUCH AS SHOES AND
 BELTS.
 EYE CONTACT FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER, ESPECIALLY
 UNDER LIDS FOR AT LEAST 15 MINUTES. IF IRRITATION OR OTHER
 EFFECTS PERSIST, OBTAIN MEDICAL TREATMENT.
 INGESTION IF SWALLOWED, OBTAIN MEDICAL TREATMENT IMMEDIATELY.

SECTION 5: FIRE-FIGHTING MEASURES

FLASH POINT (SETA) NONE LOWER EXPLOSIVE LIMIT NOT AVAILABLE
 UPPER EXPLOSIVE LIMIT 12.6 (%)

FIRE EXTINGUISHING MEDIA
 DRY CHEMICAL OR FOAM
 WATER FOG.
 CARBON DIOXIDE.

UNUSUAL FIRE AND EXPLOSION HAZARDS
 CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT
 OR FIRE.
 VAPORS MAY IGNITE EXPLOSIVELY AT AMBIENT TEMPERATURES.
 VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL LONG DISTANCES
 TO A SOURCE OF IGNITION AND FLASH BACK.
 VAPORS CAN FORM EXPLOSIVE MIXTURES IN AIR AT ELEVATED
 TEMPERATURES.
 CLOSED CONTAINERS MAY BURST IF EXPOSED TO EXTREME HEAT OR
 FIRE.
 MAY DECOMPOSE UNDER FIRE CONDITIONS EMITTING IRRITANT AND/OR
 TOXIC GASES.
 IN CLOSED TANKS, WATER OR FOAM MAY CAUSE
 FROTHING OR ERUPTION.

FIRE FIGHTING PROCEDURES
 WATER MAY BE USED TO COOL AND PROTECT EXPOSED CONTAINERS.
 FIREFIGHTERS SHOULD USE FULL PROTECTIVE CLOTHING, EYE
 PROTECTION, AND SELF-CONTAINED BREATHING APPARATUS.

HAZARDOUS DECOMPOSITION OR COMBUSTION PRODUCTS
 CARBON MONOXIDE, CARBON DIOXIDE, TOXIC GASES, ACRYLIC
 MONOMERS.
 PROPIONALDEHYDE.

SECTION 6 ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED
 COMPLY WITH ALL APPLICABLE HEALTH AND ENVIRONMENTAL
 REGULATIONS.
 ELIMINATE ALL SOURCES OF IGNITION. VENTILATE AREA. USE
 NON-SPARKING TOOLS. EVACUATE ALL UNNECESSARY PERSONNEL.
 PLACE COLLECTED MATERIAL IN PROPER CONTAINER. SPILLED
 MATERIAL IS EXTREMELY SLIPPERY. COMPLETE PERSONAL
 PROTECTIVE EQUIPMENT MUST BE USED DURING CLEANUP.
 LARGE SPILLS - SHUT OFF LEAK IF SAFE TO DO SO. DIKE AND
 CONTAIN SPILL. PUMP TO STORAGE OR SALVAGE VESSELS. USE
 ABSORBENT TO PICK UP EXCESS RESIDUE. KEEP SALVAGEABLE
 MATERIAL AND RINSE WATER OUT OF SEWERS AND WATER COURSES.
 SMALL SPILLS - USE ABSORBENT TO PICK UP RESIDUE AND DISPOSE
 OF PROPERLY.

SECTION 7 HANDLING AND STORAGE

HANDLING AND STORAGE

STORE BELOW 100F (38C). KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME. KEEP FROM FREEZING.

KEEP AWAY FROM DIRECT SUNLIGHT, HEAT AND ALL SOURCES OF IGNITION.

OTHER PRECAUTIONS USE ONLY WITH ADEQUATE VENTILATION. DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN. AVOID CONTACT WITH SKIN AND EYES, AND BREATHING OF VAPORS. WASH HANDS THOROUGHLY AFTER HANDLING, ESPECIALLY BEFORE EATING OR SMOKING. KEEP CONTAINERS TIGHTLY CLOSED AND UPRIGHT WHEN NOT IN USE. GROUND EQUIPMENT WHEN TRANSFERRING TO PREVENT ACCUMULATION OF STATIC CHARGE.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

COMMON NAME : SILICA, GEL, AMORPHOUS

CAS NUMBER: 112926-00-8

OSHA(TWA): .8 MG/M3

COMMON NAME : TITANIUM DIOXIDE

CAS NUMBER: 13463-67-7

ACGIH(TWA): 10 MG/M3 OSHA(TWA): 10 MG/M3

OSHA PEL FOR AMORPHOUS SILICA IS 80 MG/M3 DIVIDED BY % SIO₂.

RESPIRATORY PROTECTION

CONTROL ENVIRONMENTAL CONCENTRATIONS BELOW APPLICABLE EXPOSURE STANDARDS WHEN USING THIS MATERIAL. WHEN RESPIRATORY PROTECTION IS DETERMINED TO BE NECESSARY, USE A NIOSH/MSHA (CANADIAN Z94.4) APPROVED ELASTOMERIC SEALING-SURFACE FACEPIECE RESPIRATOR OUTFITTED WITH ORGANIC VAPOR CARTRIDGES AND PAINT SPRAY (DUST/MIST) PREFILTERS. DETERMINE THE PROPER LEVEL OF PROTECTION BY CONDUCTING APPROPRIATE AIR MONITORING. CONSULT 29CFR1910.134 FOR SELECTION OF RESPIRATORS (CANADIAN Z94.4).

VENTILATION PROVIDE DILUTION VENTILATION OR LOCAL EXHAUST TO PREVENT BUILD-UP OF VAPORS.

USE NON-SPARKING EQUIPMENT.

PERSONAL PROTECTIVE EQUIPMENT

EYE WASH, SAFETY SHOWER, SAFETY GLASSES OR GOGGLES. IMPERVIOUS GLOVES, IMPERVIOUS CLOTHING.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

VAPOR PRESSURE:	NOT AVAILABLE	SPECIFIC GRAVITY:	1.198
BOILING RANGE (F/C):	212-501/100-261	WEIGHT PER GALLON:	9.98/ 11.99IMP
%VOLATILE BY VOLUME:	87.56		
PHYSICAL STATE:	LIQUID	APPEARANCE	WHITE
SOLUBILITY IN WATER:	NOT AVAILABLE	PH:	NOT AVAILABLE

SECTION 10: STABILITY AND REACTIVITY

UNDER NORMAL CONDITIONS

STABLE

SEE SECTION 5 FIRE FIGHTING MEASURES

MATERIALS TO AVOID

OXIDIZERS, ACIDS, HYDROGEN CHLORIDE, NITRIC ACID, HYDROFLUORIC ACID, VINYL POLYMERS, METAL COMPOUNDS, HYDROGEN FLUORIDE, MAGNESIUM.

CONDITIONS TO AVOID

ELEVATED TEMPERATURES, CONTACT WITH OXIDIZING AGENT, FREEZING, SPARKS, OPEN FLAME, IGNITION SOURCES.

HAZARDOUS POLYMERIZATION

WILL NOT OCCUR

SECTION 11: TOXICOLOGICAL INFORMATION

COMMON NAME : SILICA, GEL, AMORPHOUS

CAS NUMBER: 112926-00-8

CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO
 LD50:>2000.00 MG/KG SKN RBT
 LD50:> 31.60 GM/KG ORL RAT
 LC50:> 2.00 PPM IHL RAT

COMMON NAME : TITANIUM DIOXIDE
 CAS NUMBER: 13463-67-7

CARCINOGENICITY LISTED BY: NTP YES 2B IARC YES 2B OSHA NO ACGIH NO
 LD50: 24.00 GM/KG ORL RAT
 LC50: 6820.00 MG/M3/4HR IHL RAT

COMMON NAME : TEXANOL
 CAS NUMBER: 25265-77-4

CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO
 LD50: 3200.00 MG/KG ORL RAT
 LD50:> 20.00 ML/KG SKN GPG

COMMON NAME : PROPYLENE GLYCOL
 CAS NUMBER: 57-55-6

CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO
 LD50: 20.00 GM/KG ORL RAT
 LD50: 20.80 GM/KG SKN RBT

SUPPLEMENTAL HEALTH INFORMATION

NO ADDITIONAL EFFECTS ARE ANTICIPATED
 CARCINOGENICITY IN A LIFETIME INHALATION STUDY, EXPOSURE TO 250 MG/M3 TITANIUM DIOXIDE RESULTED IN THE DEVELOPMENT OF LUNG TUMORS IN RATS. THESE TUMORS OCCURRED ONLY AT DUST LEVELS THAT OVERWHELMED THE ANIMALS' LUNG CLEARANCE MECHANISMS AND WERE DIFFERENT FROM COMMON HUMAN LUNG TUMORS IN BOTH TYPE AND LOCATION. THE RELEVANCE OF THESE FINDINGS TO HUMANS IS UNKNOWN BUT QUESTIONABLE.
 THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC) HAS CLASSIFIED TITANIUM DIOXIDE AS POSSIBLY CARCINOGENIC TO HUMANS (GROUP 2B) BASED ON INADEQUATE EVIDENCE OF CARCINOGENICITY IN HUMANS AND SUFFICIENT EVIDENCE OF CARCINOGENICITY IN EXPERIMENTAL ANIMALS.

REPRODUCTIVE EFFECTS NO REPRODUCTIVE EFFECTS ARE ANTICIPATED
 MUTAGENICITY NO MUTAGENIC EFFECTS ARE ANTICIPATED
 TERATOGENICITY NO TERATOGENIC EFFECTS ARE ANTICIPATED

SECTION 12: ECOLOGICAL INFORMATION

NO ECOLOGICAL TESTING HAS BEEN DONE BY AKZO NOBEL PAINTS LLC ON THIS PRODUCT AS A WHOLE.

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL DISPOSE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS. AVOID DISCHARGE TO NATURAL WATERS.

SECTION 14: TRANSPORT INFORMATION

DOT PAINT ** PROTECT FROM FREEZING **
 IMDG NOT AVAILABLE
 IATA NOT AVAILABLE
 TDG NOT AVAILABLE

SECTION 15: REGULATORY INFORMATION

SARA SARA CERCLA HAZ AIR MARINE
 302 313 302.4 POLLUTANT POLTNT
 THIS PRODUCT CONTAINS NO SARA 302, CERCLA 302.4 OR HAZARDOUS AIR POLLUTANT CHEMICALS. IT ALSO CONTAINS NO CHEMICALS WHICH ARE SUBJECT TO THE REPORTING REQUIREMENTS UNDER SARA 313.
 AS OF THE DATE OF THIS MSDS, ALL OF THE COMPONENTS IN THIS PRODUCT ARE LISTED (OR ARE OTHERWISE EXEMPT FROM LISTING) ON THE TSCA INVENTORY.
 THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE

HAZARD CRITERIA OF THE CPR (CONTROLLED PRODUCTS REGULATIONS) AND THE MSDS CONTAINS ALL THE INFORMATION REQUIRED BY THE CPR.

SECTION 16: OTHER INFORMATION

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA AVAILABLE AT THE TIME OF PREPARATION OF THIS DATA SHEET AND WHICH AKZO NOBEL PAINTS LLC BELIEVES TO BE RELIABLE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA. AKZO NOBEL PAINTS LLC SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS INFORMATION, OR OF ANY PRODUCT, METHOD OR APPARATUS MENTIONED AND YOU MUST MAKE YOUR OWN DETERMINATION OF ITS SUITABILITY AND COMPLETENESS FOR YOUR OWN USE, FOR THE PROTECTION OF THE ENVIRONMENT, AND THE HEALTH AND SAFETY OF YOUR EMPLOYEES AND USERS OF THIS MATERIAL.

COMPLIES WITH OSHA HAZARD COMMUNICATION STANDARD 29CFR1910.1200.